




А	В
280 mm	330 mm



DFU180

А	В	С	D
80 mm	35 mm	231 mm	292 mm

Е	F
78 mm	7/16-24UNS

GENERAL INFO DESIGNED FOR RAINWATER SUPPLIES

Undersink Water Filter System with High Loop Faucet

The Puretec Ecotrol™ ES2 Series is designed for alternative water supplies. It turns your rain or bore water into safe, delicious, great tasting water for cooking and drinking.

It uses ceramic cartridge technology to physically filter harmful bacteria (E. Coli, Shigella, Salmonella, Klebsiella, Cholera), lead, chlorine taste & odour, turbidity and sediment down to 0.2 micron. The cartridge is silver impregnated to prevent bacterial growth.

This economical filter system will easily fit under your existing kitchen bench. The system includes a dedicated filter faucet and standard plumbing fittings for easy installation

SPECIFICATIONS

Model·	FCO
Model:	ES2
Micron Rating:	0.2 micron
Replacement Cartridge:	
Sediment Removal	PL011
Taste & Odour Removal	CE941
Max Flow:	4 Lpm
Max Temp:	52°C
Max Pressure:	500* kPa
Connection:	¼" Quick Connect
Required hole for the tap:	12.5 mm dia.
Warranty:	3 years

Important Note: Use only genuine Puretec replacement cartridges. ^3 Year Platinum Protection applies to Puretec Systems when used in conjunction with a Puretec filter cartridge. Warranty excludes cartridges. "Where line pressure exceeds 500 kPa, an approved pressure limiting device must be installed to comply with Australian & New Zealand Plumbing Standards. (Ref. AS/NZS 3500.1:2021, Clause 3.3.4).

FEATURES & BENEFITS

- Quick and easy installation.
- Turns your rainwater into pure, safe, delicious and healthy drinking water!
- Designed for alternative water supplies where no power supply is available.
- · Washable cartridges.
- Uses ceramic cartridge technology to physically filter harmful bacteria
- Silver impregnated to prevent bacteria growth to provide safe, great tasting water on tap anytime.
- · No power required.