



GENERAL INFO **SPECIALTY WOUND SEDIMENT CARTRIDGES**

The Puretec WD Specialty Series (WD-H) is capable of withstanding temperatures of up to 149°C (300 °F) and will accommodate high flow rates, with minimal pressure drop. These cartridges are suitable for a wide variety of sediment filtration applications.

The Puretec WD Specialty Series is wound in a precise pattern around the core, providing great surface area. The result is higher dirt-holding capacity and greater efficiency than standard 2.5" x 10" wound cartridges.

FEATURES & BENEFITS

- Made from cotton material.
- 304 stainless steel core.
- String-wound design reduces fine sediment from a variety of fluids.
- Excellent particulate reduction with true depth filtration.
- Hot water models for water above 74°C.
- Carbon models for chemical, taste and odour removal.
- Minimal fibre migration.

SPECIFICATIONS AND PERFORMANCE DATA

	Model	Description	Micron Rating	Flow (Lpm)	Size
10"	WD011-H	Hot water model	1	26	standard 2.5" x 10"
	WD051-G	Granular carbon	5	27	standard 2.5" x 10"
	WD051-H	Hot water model	5	27	standard 2.5" x 10"
	WD251-H	Hot water model	25	39	standard 2.5" x 10"
20"	WD052-G	Granular carbon	5	54	standard 2.5" x 20"